

DATA SHEET-AD 7229

AD 7229 is a medium performance, strong, polyethylene coated waterproof cloth tape, coated with a pressure sensitive adhesive.

AD 7229 is available in a full range of colours including black, white, silver, grey, red, yellow, blue, green and

APPLICATIONS:

Duct sealing – covering joints in hot air and insulating material
 Fixing and holding of wires and cables, especially on film sets
 Heavy duty and export packaging for drum sealing and colour coding
 Double glazing unit sealing
 Masking applications
 Carpet joining and edging
 Colour coding and identification
 Holding and fixing of cables and wires
 Joining and splicing applications
 Ideal for general purpose applications where added strength and performance required

STEANDARD PRESENTATION:

Thickness	0,3 mm
Roll length (m)	25, 50
Roll width (mm)	19,25,38, 50, 75, 100
Core	Cardboard
Packaging	Bulk packed using interleaving sheets between layers

TECHNICAL PROPERTIES:

	Unit	Nominal value	Test Method
Tensile strength	N/cm	48	IEC 454-2
Adhesion to steel	N/cm	4	IEC 454-2
Adhesion to baking	N/cm	2,5	IEC 454-2

RECOMMENDATIONS:

The rolls should be stored flat on their cut edges in the original packaging, until required for use.
 The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.
 Service life will vary with conditions of use and affected by climatic environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions.
 Usage is recommended within one year.